



2025 TSX 561 i Series Specifications

	TSX 561 i Finish Cut Deck	TSX 561 i All-terrain Deck	
Engine	Engine	Kawasaki® FX EFI	Kawasaki® FX EFI
	Horsepower	29.5 hp	29.5 hp
	Displacement	852 cc	852 cc
	Cylinders	2	2
	Air Filter	Multi-Stage Canister	Multi-Stage Canister
	Fuel	Gasoline	Gasoline
	Fuel Capacity	8.5 gallons	8.5 gallons
	Fuel Tank	RH Side, Single	RH Side, Single
Drive Line	Transmission Type	Hydrostatic	Hydrostatic
	Transmission	Parker TF 195cc Wheel Motors and Hydro-Gear PR 16cc Pumps	Parker TF 195cc Wheel Motors and Hydro-Gear PR 16cc Pumps
	Max Forward Speed	Up to 10 mph	Up to 10 mph
	Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires
	Rear Track Size	11" x 74" Track	11" x 74" Track
Dimension/ Weight	Length	75"	75"
	Width (Chute Up)	62.5"	62.5"
	Height	50"	50"
	Weight	1450 lbs	1450 lbs
Cutting Deck	Cutting Width	61"	61"
	Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel HV All-Terrain Deck
	Deck Thickness	Laminated 10 and 7 Gauge	Laminated 7 and 7 Gauge
	Deck Depth	5.5"	6"
	Cut Height (Min - Max)	2.5" - 6"	2.5" - 5.5"
	Cutting Height Steps	1/4" Increments	1/4" Increments
	Number of Blades	3	6
	Blade Speed	17,250 fpm	17,250 fpm
	Deck Lifting System	Manual	Manual
	Clutch Torque	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner	
Warranty	Homeowner/ Commercial 3 Year Unlimited Engine 2 Year Unlimited Transmission 1 Year Manufacturer		

Additional Features

TorqFlex™ Front Suspension
 Torsion Axle Rear Suspension
 Fully Adjustable Coil Springs Over Gas Shock Rider Platform
 Ergonomically Adjustable Steering Controls

Electric Dial Throttle
 Soft Start Clutch Engagement
 Keyless Push-to-Start
 SmarTrac™ Pro Display
 Turf Track