

| TFX | | | |
|-----|--|--|--|
| | | | |
| | | | |

| | IFX /bb i (Al-lerraFlex) | | | | |
|---------------------------|---------------------------------------|--|--|--|--|
| p/n | 1055249 | | | | |
| Engine | Kawasaki® FX EFI | | | | |
| Horsepower | 38.5 hp | | | | |
| Displacement | 999 сс | | | | |
| Cylinders | 2 | | | | |
| Air Filter | 5" Cyclonic | | | | |
| Fuel | Gasoline | | | | |
| Fuel Capacity | 14 gallons | | | | |
| Fuel Tank | Rear, Single | | | | |
| Transmission Type | Hydrostatic | | | | |
| Transmission | Hydro-Gear ZT-5400 High/Low Range | | | | |
| Max Forward Speed | 11 mph | | | | |
| Front Tire Size | 15" Flat-Free Tires | | | | |
| Rear Track Size | 10" x 81" All-Terrain TerraFlex Track | | | | |
| Length | 96" | | | | |
| Width (Chute Up) | 67.5" | | | | |
| Height (ROPS Up) | 79" | | | | |
| Weight | N/A | | | | |
| Cutting Width | 66" | | | | |
| Deck Construction | Fabricated Steel HV All-Terrain Deck | | | | |
| Deck Thickness | Laminated 7 and 7 Gauge | | | | |
| Deck Depth | 6" | | | | |
| Cut Height (Min - Max) | 3" - 7" | | | | |
| Cutting Height Steps | 1/4" Increments | | | | |
| Number of Blades | 6 All-Terrain Blades | | | | |
| Blade Speed | 18,500 fpm | | | | |
| Anti-Scalp Wheels | n/a | | | | |
| Deck Lifting System | Manual | | | | |
| Clutch Torque | 250 ft-lbs | | | | |
| Clutch Manufacturer | Warner | | | | |
| | | | | | |

Additional Features