



2026 TRX 354/561 i Series Specifications

	TRX 354	TRX 561 i All-Terrain Deck	TRX 561 i Finish Cut Deck
p/n	1055242	1055244	1055243
Engine	Kawasaki® FT	Kawasaki® FX EFI	Kawasaki® FX EFI
Horsepower	24 hp	29.5 hp	29.5 hp
Displacement	726 cc	852 cc	852 cc
Cylinders	2	2	2
Air Filter	Multi-Stage Canister	Multi-Stage Canister	Multi-Stage Canister
Fuel	Gasoline	Gasoline	Gasoline
Fuel Capacity	10 gallons	14 gallons	14 gallons
Fuel Tank	Side, Double	Side, Double	Side, Double
Transmission Type	Hydrostatic	Hydrostatic	Hydrostatic
Transmission	Hydro-Gear ZT-3400	Hydro-Gear ZT-4400	Hydro-Gear ZT-4400
Max Forward Speed	8 mph	9 mph	9 mph
Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires	13" Flat-Free Tires
Rear Track Size	11" x 68" Turf Track	10" x 72" All-Terrain TerraFlex Track	10" x 72" Turf TerraFlex Track
Length	84.5"	93"	93"
Width (Chute Up)	55"	62"	62"
Height (ROPS Up)	76"	79"	79"
Weight	1220 lbs	1600 lbs	1540 lbs
Cutting Width	54"	61"	61"
Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel HV All-Terrain Deck	Fabricated Steel Aero Deck
Deck Thickness	Laminated 10 and 10 Gauge	Laminated 7 and 7 Gauge	Laminated 10 and 7 Gauge
Deck Depth	4.5"	6"	5.5"
Cut Height (Min - Max)	2.25" - 5"	3" - 7"	2.5" - 6"
Cutting Height Steps	1/4" Increments	1/4" Increments	1/4" Increments
Number of Blades	3	6 All-Terrain Blades	3
Blade Speed	18,500 fpm	18,500 fpm	18,500 fpm
Anti-Scalp Wheels	5 Recessed	n/a	6 Recessed
Deck Lifting System	Manual	Manual	Manual
Clutch Torque	200 ft-lbs	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner	Warner
Homeowner/ Commercial	3 Year Unlimited Hours Engine 2 Year Unlimited Hours Transmission 1 Year Manufacturer		

Additional Features

TorqFlex™ Front Suspension*
12-way Adjustable Suspension Seat
SmarTrac™ Pro Display*
Soft Start Clutch Engagement*
Keyless Push-to-Start*

Oil Warning Light*
No Slip Floor Mat
Rear Hitch installed on TRX 354 models
Torsion Axle Rear Suspension

*TRX 561 i models only.

Optional Independent Front Suspension available for TRX 354 models.



2026 TRX 766 i Series Specifications

	TRX 766 i All-Terrain Deck	TRX 766 i Finish Cut Deck
p/n	1055248	1055247
Engine	Kawasaki® FX EFI	Kawasaki® FX EFI
Horsepower	38.5 hp	38.5 hp
Displacement	999 cc	999 cc
Cylinders	2	2
Air Filter	5" Cyclonic	5" Cyclonic
Fuel	Gasoline	Gasoline
Fuel Capacity	14 gallons	14 gallons
Fuel Tank	Side, Double	Side, Double
Transmission Type	Hydrostatic	Hydrostatic
Transmission	Hydro-Gear ZT-5400 High/Low Range	Hydro-Gear ZT-5400 High/Low Range
Max Forward Speed	11 mph	11 mph
Front Tire Size	15" Flat-Free Tires	15" Flat-Free Tires
Rear Track Size	10" x 81" All-Terrain TerraFlex Track	10" x 81" Turf TerraFlex Track
Length	96"	96"
Width (Chute Up)	67.5"	67.5"
Height (ROPS Up)	79"	79"
Weight	1800 lbs	1780 lbs
Cutting Width	66"	66"
Deck Construction	Fabricated Steel HV All-Terrain Deck	Fabricated Steel Aero Deck
Deck Thickness	Laminated 7 and 7 Gauge	Laminated 10 and 7 Gauge
Deck Depth	6"	5.5"
Cut Height (Min - Max)	3" - 7"	2.5" - 6"
Cutting Height Steps	1/4" Increments	1/4" Increments
Number of Blades	6 All-Terrain Blades	3
Blade Speed	18,500 fpm	18,500 fpm
Anti-Scalp Wheels	n/a	6 Recessed
Deck Lifting System	Manual	Manual
Clutch Torque	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner
Homeowner/ Commercial	3 Year Unlimited Hours Engine 2 Year Unlimited Hours Transmission 1 Year Manufacturer	

Additional Features

TorqFlex™ Front Suspension
12-way Adjustable Suspension Seat
Hour Meter/Tachometer

Oil Warning Light
No Slip Floor Mat
TerraFlex® Turf/All-Terrain Tracks
Torsion Axle Rear Suspension