



2026 TSX 561 i Series Specifications

	TSX 561 i Finish Cut Deck	TSX 561 i All-terrain Deck
p/n	1055245	1055246
Engine	Kawasaki® FX EFI	Kawasaki® FX EFI
Horsepower	29.5 hp	29.5 hp
Displacement	852 cc	852 cc
Cylinders	2	2
Air Filter	Multi-Stage Canister	Multi-Stage Canister
Fuel	Gasoline	Gasoline
Fuel Capacity	8.5 gallons	8.5 gallons
Fuel Tank	RH Side, Single	RH Side, Single
Transmission Type	Hydrostatic	Hydrostatic
Transmission	Parker TF 195cc Wheel Motors and Hydro-Gear PR 16cc Pumps	Parker TF 195cc Wheel Motors and Hydro-Gear PR 16cc Pumps
Max Forward Speed	Up to 10 mph	Up to 10 mph
Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires
Rear Track Size	10" x 72" Turf TerraFlex Track	10" x 72" All-Terrain TerraFlex Track
Length	75"	75"
Width (Chute Up)	62.5"	62.5"
Height	50"	50"
Weight	1560 lbs	1545 lbs
Cutting Width	61"	61"
Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel HV All-Terrain Deck
Deck Thickness	Laminated 10 and 7 Gauge	Laminated 7 and 7 Gauge
Deck Depth	5.5"	6"
Cut Height (Min - Max)	2.5" - 6"	2.5" - 5.5"
Cutting Height Steps	1/4" Increments	1/4" Increments
Number of Blades	3	6
Blade Speed	17,250 fpm	17,250 fpm
Deck Lifting System	Manual	Manual
Clutch Torque	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner
Homeowner/ Commercial	3 Year Unlimited Hours Engine 2 Year Unlimited Hours Transmission 1 Year Manufacturer	

Additional Features

TorqFlex™ Front Suspension
 Torsion Axle Rear Suspension
 Fully Adjustable Coil Springs Over Gas Shock Rider Platform
 Ergonomically Adjustable Steering Controls

Electric Dial Throttle
 Oil Warning Light
 Hour Meter / Tachometer