



2026 XP RD i / XP SSi Series Specifications

	XP 610 RD i	XP 610 SSi
p/n	1055237	1055251
Engine	Kawasaki® FX EFI	Kawasaki® FX EVO EFI
Horsepower	29.5 hp	34.5 hp
Displacement	852 cc	822 cc
Cylinders	2	2
Air Filter	Heavy Duty	Heavy Duty
Fuel	Gasoline	Gasoline
Fuel Capacity	14 gallons	14 gallons
Fuel Tank	Side, Double	Side, Double
Transmission Type	Hydrostatic	Hydrostatic
Transmission	Hydro-Gear ZT-4400	Hydro-Gear ZT-4400
Max Forward Speed	11 mph	11 mph
Front Tire Size	13" Flat Free	13" Flat Free
Rear Tire Size	24"	24"
Length	83.5"	83.5"
Width (Chute Up)	62"	62"
Height (ROPS Up)	73.5"	73.5"
Weight	1410 lbs	1415 lbs
Cutting Width	61"	61"
Deck Construction	Fabricated Steel Aero Deck Rear Discharge	Fabricated Steel Aero Deck Rear Discharge
Deck Thickness	Laminated 10 and 7 Gauge	Laminated 10 and 7 Gauge
Deck Depth	5"	5"
Cut Height (Min - Max)	1.5" - 5"	1.5" - 5"
Cutting Height Steps	1/4" Increments	1/4" Increments
Number of Blades	3	3
Blade Speed	18,500 fpm	18,500 fpm
Anti-Scalp Wheels	6 Recessed	6 Recessed
Deck Lifting System	Manual	Manual
Clutch Torque	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner
Homeowner/ Commercial	3 Year Unlimited Hours Engine 2 Year Unlimited Hours Transmission 3-Year/1500 Hours First 2-Years No Hour Limitation	
Rental	90 days	90 days

Additional Features

TorqFlex™ Front Suspension (XP 610 RD i)
Tri-Axis™ Front Suspension (XP 610 SSi)
High-Visibility Safety Color (XP 610 SSi)
Seat Suspension
Hour Meter / Tachometer (XP 610 SSi)
SmarTrac™ Pro Display (XP 610 RD i)

Soft Start Clutch Control (XP 610 RD i)
Keyless Push-to-Start (XP 610 RD i)
Rear Discharge (XP 610 RD i)
Heavy Duty Spindles
No Slip Floor Mat



2026 XP HD Series Specifications

	XP 540 HD	XP 610 HD i	XP 660 HD	XP 720 HD
p/n	1055235	1055236	1055238	1055239
Engine	Kawasaki® FX	Kawasaki® FX EFI	Kawasaki® FX	Kawasaki® FX
Horsepower	27 hp	29.5 hp	35 hp	35 hp
Displacement	852 cc	852 cc	999 cc	999 cc
Cylinders	2	2	2	2
Air Filter	Multi-Stage Canister	Heavy Duty	Multi-Stage Canister	Multi-Stage Canister
Fuel	Gasoline	Gasoline	Gasoline	Gasoline
Fuel Capacity	14 gallons	14 gallons	14 gallons	14 gallons
Fuel Tank	Side, Double	Side, Double	Side, Double	Side, Double
Transmission Type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Transmission	Hydro-Gear ZT-4400	Hydro-Gear ZT-4400	Hydro-Gear ZT-4400	Hydro-Gear ZT-4400
Max Forward Speed	11 mph	11 mph	11 mph	11 mph
Front Tire Size	13"	13"	13"	13"
Rear Tire Size	24"	24"	24"	24"
Length	83.5"	83.5"	85"	86.5"
Width (Chute Up)	55"	62"	67"	73"
Height (ROPS Up)	73.5"	73.5"	73.5"	73.5"
Weight	1330 lbs	1355 lbs	1400 lbs	1415 lbs
Cutting Width	54"	61"	66"	72"
Deck Construction	Fabricated Steel Aero Deck	Fabricated Steel Aero Deck	Fabricated Steel Aero Deck	Fabricated Steel Aero Deck
Deck Thickness	Laminated 10 and 7 Gauge	Laminated 10 and 7 Gauge	Laminated 10 and 7 Gauge	Laminated 10 and 7 Gauge
Deck Depth	5"	5"	5"	5"
Cut Height (Min - Max)	1.5" - 5"	1.5" - 5"	1.5" - 5"	1.5" - 5"
Cutting Height Steps	1/4" Increments	1/4" Increments	1/4" Increments	1/4" Increments
Number of Blades	3	3	3	3
Blade Speed	18,500 fpm	18,500 fpm	18,500 fpm	18,500 fpm
Anti-Scalp Wheels	6 Recessed	6 Recessed	6 Recessed	8 Recessed
Deck Lifting System	Manual	Manual	Manual	Manual
Clutch Torque	250 ft-lbs	250 ft-lbs	250 ft-lbs	250 ft-lbs
Clutch Manufacturer	Warner	Warner	Warner	Warner
Homeowner/ Commercial	3 Year Unlimited Hours Engine 2 Year Unlimited Hours Transmission 3-Year/1500 Hours First 2-Years No Hour Limitation			
Rental	90 days	90 days	90 days	90 days

Additional Features

TorqFlex™ Front Suspension
Seat Suspension
SmarTrac™ Pro Display
Heavy Duty Spindles

Soft Start Clutch Control
Keyless Push-to-Start
No Slip Floor Mat