



TRX Series Specifications

	TRX 354	TRX 561	TRX 766 i Finish Cut Deck	TRX 766 i All-terrain Deck	
Engine	Engine	Kawasaki® FT	Kawasaki® FX	Briggs & Stratton Vanguard™ EFI	
	Horsepower	27 hp	31 hp	37 hp	
	Displacement	726 cc	999 cc	993 cc	
	Cylinders	2	2	2	
	Air Filter	Multi-Stage Canister	Multi-Stage Canister	5" Cyclonic	5" Cyclonic
	Fuel	Gasoline	Gasoline	Gasoline	Gasoline
	Fuel Capacity	10 gallons	14 gallons	14 gallons	14 gallons
	Fuel Tank	Side, Double	Side, Double	Side, Double	Side, Double
Drive Line	Transmission Type	Hydrostatic	Hydrostatic	Hydrostatic	
	Transmission	Hydro-Gear ZT-3400	Hydro-Gear ZT-4400	Hydro-Gear ZT-5400	
	Max Forward Speed	8 mph	9 mph	11 mph	11 mph
	Front Tire Size	13" Flat-Free Tires	13" Flat-Free Tires	15" Flat-Free Tires	15" Flat-Free Tires
	Rear Track Size	11" x 71" Track	11" x 74" Track	11" x 81" Track	11" x 81" Track
Dimension/ Weight	Length	84.5"	93"	96"	
	Width (Chute Up)	55"	62"	67.5"	
	Height (ROPS Up)	76"	79"	79"	79"
	Weight	1220 lbs	1540 lbs	1600 lbs	1600 lbs
Cutting Deck	Cutting Width	54"	61"	66"	
	Deck Construction	Fabricated Steel	Fabricated Steel	Fabricated Steel	Fabricated Steel All-Terrain Deck
	Deck Thickness	Laminated 10 and 10 Gauge	Laminated 10 and 7 Gauge	Laminated 10 and 7 Gauge	Laminated 7 and 7 Gauge
	Deck Depth	4.5"	5.5"	5.5"	6"
	Cut Height (Min - Max)	2.25" - 5"	2.5" - 6"	2.5" - 6"	3" - 7"
	Cutting Height Steps	1/4" Increments	1/4" Increments	1/4" Increments	1/4" Increments
	Number of Blades	3	3	3	6 All-Terrain Blades
	Blade Speed	18,500 fpm	18,500 fpm	18,500 fpm	18,500 fpm
	Anti-Scalp Wheels	5 Recessed	6 Recessed	6 Recessed	n/a
	Deck Lifting System	Manual	Manual	Manual	Manual
Clutch Torque	200 ft-lbs	250 ft-lbs	250 ft-lbs	250 ft-lbs	
Clutch Manufacturer	Warner	Warner	Warner	Warner	
Warranty	Homeowner/ Commercial	3 year engine / 2 year transmission, 1 year manufacturer warranty	3 year engine / 2 year transmission, 1 year manufacturer warranty	3 year engine / 2 year transmission, 1 year manufacturer warranty	

Additional Features

TorqFlex™ Front Suspension*
 12-way Adjustable Suspension Seat
 SmarTrac™ Pro Display*
 Soft Start Clutch Engagement*

Keyless Push-to-Start*
 Oil Warning Light*
 No Slip Floor Mat
 Rear Hitch installed on TRX 354 models

*TRX 561 and TRX 766 models only.
 Optional Independent Front Suspension available for TRX 354 models.